



TABLETOP DRY ERASE PAD



2 in 1

DRY ERASE & PAD

POST-IT EASEL PAD



3M

DCOF... (DYNAMIC COEFF. OF FRICTION)... WHAT TO LOOK FOR?

BOT 3000
X-ANSI 137.1
NOW ANSI 326.3



RAMP TEST
DIN 51130 & 51097



BRITISH PENDULUM
BS EN 13036



MINIMUM REQUIREMENT
INDOOR FLAT SURFACE

0.42 OR ABOVE

MINIMUM REQUIREMENT
INDOOR FLAT SURFACE

R9 (R11 IF WET)

MINIMUM REQUIREMENT
INDOOR FLAT SURFACE

IT DEPENDS. A VERY CLEAR CHART EXPLAINS EACH GIVEN SITUATION FROM PTV 12 TO PTV 35

MIN. REQ. OUTDOOR APP.

TEST DOES NOT SPECIFY.
NOT RELIABLE

MIN. REQ. OUTDOOR APP.

R11 → DIN 51130

IF A POOL DECK A+B IS REQUIRED DIN 51097 (BARE FOOT TEST)

MIN. REQ. OUTDOOR APP.

PTV 45 (HARD RUBBER / SHOES)

PTV 40 (SOFT RUBBER / BARE FOOT)

AGAIN PLS. CHECK CHART

NOTE:

- LOWER THAN 0.42 INDOOR USE IS ADMITTED IF MEASURES ARE IN PLACE TO KEEP FLOOR DRY
- NO GUIDANCE FOR INDOOR WET AREAS, RAMPS ETC.

NOTE:

- INDOOR DRY R9
- INDOOR TRANSITIONAL R10
- INDOOR WET OR OUTDOOR R11 A+B
- R12, R13 PLS. SEE TEST

NOTE:

- THE MOST ACCURATE TEST
- CAN TEST ON JOBSITE
- VERY SPECIFIC WHICH VALUE TO USE IN EVERY SITUATION
- C.T.I.O.A ALSO ADOPTS IT

ANSI 326.3 DOES NOT GIVE GUIDELINES... BARELY SOME NUMBERS...



TABLETOP DRY ERASE PAD



2 in 1

DRY ERASE & EASEL PAD



20 20 IN x 23 IN (50,8 cm x 58,4 cm)

1 DRY ERASE SHEET 20 IN x 21 IN (50,8 cm x 53,3 cm)

3M